

# Large Format Print iPF760

## Excellent Features That Meet Your Demands

Professional print solution offer efficiencies, productivity and ease of use. Delivers sharp, vivid with high volume output and robust security settings.



### Ease of Use

|                |            |                              |
|----------------|------------|------------------------------|
| 130ml Ink Tank | Roll Paper | HP-GL/2<br>HP RTL<br>Support |
|----------------|------------|------------------------------|

|                          |                            |
|--------------------------|----------------------------|
| Gigabit Ethernet Support | Max Length Print(RIP) 175M |
|--------------------------|----------------------------|



### Print Speed

| Size              | Paper       | Mode           | Print Speed        |
|-------------------|-------------|----------------|--------------------|
| A0                | Plain paper | Draft (300dpi) | Approx. 46 seconds |
| A0 <sup>CAD</sup> | Plain paper | Draft (600dpi) | Approx. 48 seconds |

## KEY FEATURES

### High Productivity

- Fast throughput
- Low running cost
- Economy Printing Mode
- Ink tank replacement while printing in progress

### Exceptional Usability

- All operations accessible from front
- Installed flush against wall
- Small footprint
- Print 175m banner (RIP)
- New Media Basket

### Support CAD Quality Print

- New magenta ink & color emulation
- Printer Driver Optimization module for AutoCAD
- Enhanced HP-GL/2 support
- HP-GL/2 palette and pen settings

### Management Environment

- Accounting functions
- Increased robust security
- Notification replacement for ink tank & maintenance cartridge
- Resettable settings

# DataSheet

## imagePROGRAF iPF760 (36-inch)

|                                |                                                                                                                                                                     |                                                                          |                             |                |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|-----------------------------|----------------|
| Ink Type                       | Dye and pigment reactive ink: BK, MBK x 2, C, M (New Magenta), Y                                                                                                    |                                                                          |                             |                |
| Maximum Print Resolution       | 2400 x 1200 dpi                                                                                                                                                     |                                                                          |                             |                |
| Minimal Line Width             | 0.02 mm                                                                                                                                                             |                                                                          |                             |                |
| Line Accuracy                  | ± 0.1% or less                                                                                                                                                      |                                                                          |                             |                |
| Dimensions, Weight (Net)       | Main Unit with Stand:                                                                                                                                               | 1304 (W) x 877 (D) x 1062 (H) mm; approx 63.9kg                          |                             |                |
| Power Supply                   | Input Power:                                                                                                                                                        | AC 100 - 240 V (50-60Hz)                                                 | Standby:                    | 6 W or less    |
|                                | Power Consumption:                                                                                                                                                  | Operation : 140 W or less                                                | Power off (Stand By):       | 0.5 W or less  |
| Operation Environment          | Temperature: 15 - 30° C , Humidity: 10 - 80% (No Condensation)                                                                                                      |                                                                          |                             |                |
| Acoustic Noise                 | Asoustic Pressure:                                                                                                                                                  | Operation: Approx. 50 dB (A) or less, Standby: Approx. 35 dB (A) or less |                             |                |
|                                | Asoustic Power:                                                                                                                                                     | 6.6 Bels                                                                 |                             |                |
| Standard Memory                | 256 MB                                                                                                                                                              |                                                                          |                             |                |
| Hard Disk                      | -                                                                                                                                                                   |                                                                          |                             |                |
| Interface                      | USB2.0 Hi-Speed, 10/100/1000BASE-T/TX                                                                                                                               |                                                                          |                             |                |
| Media Handling                 | Media Feed & Output:                                                                                                                                                | Rollpaper: 1 Roll, Top Loading, Front Output                             |                             |                |
|                                | Manual Feed:                                                                                                                                                        | Top-feeding, Front Output, using Media Locking Lever                     |                             |                |
| Media Thickness                | 0.07 - 0.8mm                                                                                                                                                        |                                                                          |                             |                |
| Maximum Roll Outer Diameter    | 150mm                                                                                                                                                               |                                                                          |                             |                |
| Media Core Size                | Internal Diameter of Roll Core: 2" / 3"                                                                                                                             |                                                                          |                             |                |
| Media Width                    | Roll Paper: 254 - 914.4 mm , Cut Sheet: 203.2 - 917 mm                                                                                                              |                                                                          |                             |                |
| Maximum Printable Paper Length | Roll Paper: 18m , Cut Sheet: 1.6m                                                                                                                                   |                                                                          |                             |                |
| Printable Margins              | Roll Paper:                                                                                                                                                         | All sides: 3mm                                                           | Borderless Print:           | All sides: 0mm |
|                                | Cut Sheet:                                                                                                                                                          | Bottom: 23mm, Others 3mm                                                 |                             |                |
| Print Head                     | Model : PF-04                                                                                                                                                       | Type: Bubble-jet on demand                                               | Droplet Size: 4pl per color |                |
|                                | Nozzle Pitch: 1200 dpi x 2                                                                                                                                          | Nozzle Per Chip: MBK 5120 nozzles, each other color 2560 nozzles         |                             |                |
| Ink Tank                       | Model: PFI-102MBK/BK/C/Y, PFI-104M                                                                                                                                  |                                                                          | Colors: MBK,BK,C,M,Y        |                |
| Ink Capacity                   | Bundled Starter Ink: 90ml, Sales Ink: 130ml                                                                                                                         |                                                                          |                             |                |
| Environment Certifications     | ENERGY STAR(WW), RoHS Directive (Europe)(China), The ECO Declaration(Europe), WEEE(Europe)(India), Executive Order of the President of the United States of America |                                                                          |                             |                |



Delighting You Always

### SOUTH & SOUTHEAST ASIA REGIONAL

CANON SINGAPORE PTE. LTD.  
1 HarbourFront Avenue #04-01 Keppel Bay Tower, Singapore 098632  
Tel: 65-6799-8888 | Fax: 65-6799-8882 | www.canon-asia.com | www.canon.com.sg

#### BANGLADESH

J.A.N. Associates Ltd  
House 25, Road 5  
Dharmondi R/A  
Dhaka-1205, Bangladesh  
Tel : 880-2-8611444  
Fax : 880-2-8610410

#### BRUNEI

Interhouse Company  
No. 5-7 Bunut Jaya Complex  
Spg 574 Jalan Tutong BF1320  
P.O. Box 423, Seri Complex  
Bandar Seri Begawan BA 1779  
Brunei Darussalam  
Tel : 673-2-653001  
Fax : 673-2-653003

#### CAMBODIA

Royal Cambodia Co., Ltd  
#437 Preah Monivong Blvd  
Phnom Penh  
Kingdom of Cambodia  
Tel : 855-23-428955  
Fax : 855-23-722961

#### HONG KONG

Canon Hongkong Co.Ltd  
19F, The Metropolis Tower  
10 Metropolis Drive  
Hungghom, Hong Kong  
Tel : 825-3191-2388  
Fax: 825-2369-3800

#### INDIA

Canon India Pvt. Ltd  
7th Floor, Tower B,  
DLF Cyber Terraces,  
DLF Phase-3  
Gurgaon — 122002 Haryana, India  
Tel : 91-124-4160000  
Fax: 91-124-4160011

#### INDONESIA

PT Datascrip  
Kawasan Niaga Selatan Blok B-15  
Bandar Kemayoran, Jakarta 10610  
Indonesia  
Tel : 62-21-6544515  
Fax : 62-21-6544811 to 13

#### MALAYSIA

Canon Marketing  
(Malaysia) Sdn. Bhd.  
Block D, Peremba Square  
Saujana Resort Section U2  
40150 Shah Alam  
Selangor Darul Ehsan, Malaysia  
Tel : 60-3-78446000 / 78450055  
Fax : 60-3-78446196 / 6198

#### MALDIVES

SIMDI Company Pvt. Ltd.  
G. Faith, Majeedhee Magu,  
Male' 20-129  
Republic of Maldives  
Tel : 960-3334421  
Fax : 960-3334424

#### MYANMAR

Myanmar Golden Rock  
International Co., Ltd.  
Level 6, FJV Commercial Center  
No: 422-426, Strand Road  
Botataung Township  
Yangon, Myanmar  
Tel : 95-1-202092 to 96  
Fax : 95-1-202079

#### NEPAL

International Electronics  
Concern (P) Ltd  
Kha 14, 1st Floor  
Haratibhawan Putalisadak  
Ramshah Path, Kathmandu,  
Nepal P.O. Box 12588  
Tel : 977-1-4421991  
Fax : 977-1-4421909

#### PAKISTAN

Shirazi Trading Company (Pvt.) Ltd  
8th Floor, Adamjee House  
I.I. Chundrigar Road  
Karachi 74000 Pakistan  
Tel : 92-21-3241 (7659), (7737) or  
(7746)  
Fax : 92-21-(32417747), (32420417)  
or (32420418)

#### PHILIPPINES

Canon Marketing (Philippines), Inc.  
Ground Floor Commerce and  
Industry Plaza,  
Campus Ave. Cor. Park Ave.,  
McKinley Hill  
Fort Bonifacio, Taguig City  
Tel : 632-884-9000  
Fax : 632-556-1456

#### SRI LANKA

Metropolitan Computers (Pvt.) Ltd  
85, Braybrook Place  
Colombo 2  
Sri Lanka  
Tel : 94-11-2437797  
Fax : 94-11-2448980

#### THAILAND

Canon Marketing (Thailand)  
Co., Ltd.  
No.98 Sathorn Square Office Tower  
21st to 24th Floor, North Sathorn  
Road,  
Silom, Bangrak, Bangkok 10500  
Tel : 66-2-3449988  
Fax : 66-2-3449861

#### VIETNAM

Canon Marketing Vietnam Co. Ltd  
Floor 6, Saigon Centre Building,  
65 Le Loi, Ben Nghe Ward,  
District 1, Ho Chi Minh City,  
Vietnam  
Tel : 848-3820-0466  
Fax : 848-3820-0477

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.

CANON, IMAGEPROGRAF are registered trademarks of Canon Inc. Microsoft and Windows are registered trademarks of Microsoft Corporation in the

Web Distribution © Canon Singapore Pte Ltd 2012. All rights reserved. Printed in Singapore.